

Technical datasheet

Description

Article Number

264804

Type description REV-3POL/03-7,5kW B/G 16A, IP66, 1NC, switch 0/1+mounting kit, black/ grey

Switching diagram


On-off switch

4 switching contacts

3-pole + NC

Switching angle: 90°

Lettering O OFF - I ON



Electrical Data Switch

Rated uninterrupted current I_{the}

25 A

Rated operational current I_e AC-21A

25 A

Rated operational voltage U_e

690 V

Making/breaking capacity of AC-23A 400V

7.5 kW

Making/breaking capacity of AC-3 400V

5.5 kW

Isolating characteristic up to

500 Volt ~

Single phase motor 230V

2.2 kW

Single phase motor 400V

3 kW

Terminal cross section

- solid or multi-stranded

min./max.

1.0 - 4.0 mm²

- finely stranded with ferrule

min./max.

1.0 - 2.5 mm²

Application

Insulated enclosure I1N1551 for outdoor applications

Lockout handle for 3 padlocks lockable in O-position

Handle/front plate black/grey

Degree of protection IP 66

Dimensions (mm)

Dimensions (mm)					Knock-out		Drilled
A	C	D	E	G	H1	H2	H3
90.5	73	29	80	Ø5.5	M20	M12	M20

