

Capacity correction factors

Height difference and pipe length



R32



SYSPLIT DUCT 12-60 LNS HP

Capacity (Btu/h)		12K		Pipe Length (m)			
Cooling				5	10	20	25
Height difference H (m)	Indoor Upper than Outdoor	10			0.973	0.948	0.936
		5	0.995		0.983	0.958	0.945
		0	1.000		0.988	0.963	0.950
	Outdoor Upper than Indoor	-5	1.000		0.988	0.963	0.950
		-10			0.988	0.963	0.950
Heating				5	10	20	25
Height difference H (m)	Indoor Upper than Outdoor	10			0.993	0.978	0.970
		5	1.000		0.993	0.978	0.970
		0	1.000		0.993	0.978	0.970
	Outdoor Upper than Indoor	-5	0.992		0.985	0.970	0.962
		-10			0.977	0.962	0.955

Capacity (Btu/h)		18K		Pipe Length (m)			
Cooling				5	10	20	30
Height difference H (m)	Indoor Upper than Outdoor	20				0.928	0.912
		10			0.969	0.937	0.921
		5	0.995		0.979	0.946	0.930
		0	1.000		0.984	0.951	0.935
	Outdoor Upper than Indoor	-5	1.000		0.984	0.951	0.935
		-10			0.984	0.951	0.935
-20					0.951	0.935	
Heating				5	10	20	30
Height difference H (m)	Indoor Upper than Outdoor	20				0.982	0.976
		10			0.994	0.982	0.976
		5	1.000		0.994	0.982	0.976
		0	1.000		0.994	0.982	0.976
	Outdoor Upper than Indoor	-5	0.992		0.986	0.974	0.968
		-10			0.978	0.966	0.960
-20					0.959	0.953	

Capacity (Btu/h)	48k		Pipe Length (m)						
Cooling			5	15	25	35	50	65	75
Height difference H (m)	Indoor Upper than Outdoor	30	/	/	/	0.880	0.838	0.796	0.768
		20	/	/	0.918	0.889	0.846	0.804	0.775
		10	/	0.956	0.927	0.898	0.855	0.812	0.783
		5	0.995	0.966	0.937	0.907	0.864	0.820	0.791
		0	1.000	0.971	0.941	0.912	0.868	0.824	0.795
	Outdoor Upper than Indoor	-5	1.000	0.971	0.941	0.912	0.868	0.824	0.795
		-10	/	0.971	0.941	0.912	0.868	0.824	0.795
		-20	/	/	0.941	0.912	0.868	0.824	0.795
		-30	/	/	/	0.912	0.868	0.824	0.795
	Heating			5	15	25	35	50	65
Height difference H (m)	Indoor Upper than Outdoor	30	/	/	/	0.956	0.933	0.911	0.896
		20	/	/	0.970	0.956	0.933	0.911	0.896
		10	/	0.985	0.970	0.956	0.933	0.911	0.896
		5	1.000	0.985	0.970	0.956	0.933	0.911	0.896
		0	1.000	0.985	0.970	0.956	0.933	0.911	0.896
	Outdoor Upper than Indoor	-5	0.992	0.977	0.963	0.948	0.926	0.904	0.889
		-10	/	0.969	0.955	0.940	0.918	0.896	0.882
		-20	/	/	0.947	0.933	0.911	0.889	0.875
		-30	/	/	/	0.925	0.904	0.882	0.868